

WT1011M

Item No: T0053449699



Compact. Powerful. Versatile.
Boost your productivity
Discover the WT 1M Soldering Station, a true workaholic boosting your workspace productivity. This isn't just a tool—it's your ultimate partner for excellence. With extremely fast heat-up and recovery times, it handles everything from small components to large applications effortlessly. No more juggling tools or compromising performance. Enjoy the best value without sacrificing quality, gaining the flexibility and productivity to simplify your tasks and achieve more. Choose worry-free precision. Choose unstoppable productivity. Choose Weller WT Soldering Stations.

KEY FEATURES

- + This kit meets the need for smallest nano and pico soldering applications.
- + Compact
The WT1M is a compact, single-channel soldering station that streamlines your workspace, cuts costs, and boosts efficiency by effortlessly managing tasks from nano to larger micro applications.
- + Powerful
The Weller RTP Tips active tips series with extremely fast heat-up times boost productivity. They allow continuous workflow and faster task completion, which ultimately leads to higher efficiency and greater project throughput.
- + Versatile

The WT 1M soldering stations offer exceptional flexibility, seamlessly integrating with both new nano and micro tools with active tip technology and existing ones with passive tip technology, ensuring a flexible, user-friendly experience for all your soldering needs. It is up to your productivity and total cost of ownership preferences.

- + Fast Heat Up and Recovery Time**
3 seconds heat-up time with Weller's RTP tips with active heat technology. Fast heat-up times maximize productivity by reducing waiting periods, enabling quicker start times, continuous workflow, and faster job completion, enhancing overall efficiency and performance.
- + Multiple Options possible**
Connect 10+ different soldering tools to one WT1M soldering station, showcasing unmatched flexibility. Fast and powerful active tips or cost of ownership sensitive tools enhance efficiency without the need for multiple stations.
- + Stackable units**
WT stations can be stacked onto each other
- + Health Care**
The WT station, connected to a Weller ZeroSmog fume extraction unit, safeguards health during soldering.
- + 1 Channel Nano/Pico Soldering Kit (95 W) to cover smallest soldering tasks**
including WTPP MS Nano/Pico pencil with active (cartridge) tip technology
RTP Tip Family with 3 seconds heat-up time
High productivity
Intuitive use thanks to clear menu structure
Reduced footprint thanks to stackability
Graphical backlit LC-Display
High performance and functionality - many connectable tools
Housing cover useable as storage
OFF time, Process window, Lock function, Offset
Stackable units
Connectable to ZeroSmog Fume Extraction Units
- + 1 Channel Nano/Pico Soldering Kit (95 W) to cover smallest soldering tasks**
including WTPP MS Nano/Pico pencil with active (cartridge) tip technology
RTP Tip Family with 3 seconds heat-up time
High productivity
Intuitive use thanks to clear menu structure
Reduced footprint thanks to stackability
Graphical backlit LC-Display
High performance and functionality - many connectable tools
Housing cover useable as storage
OFF time, Process window, Lock function, Offset
Stackable units
Connectable to ZeroSmog Fume Extraction Units

Compact. Powerful. Versatile



TECHNICAL DATA

Dimensions L x W x H	150 x 130 x 101 mm
ESD Safe	Yes
Fuse	230V (mA)T500
Mil-Spec	Yes
Power Consumption	95 W
Temperature Accuracy °C	±9 °C
Temperature Range (Depends on Tool)	50 - 450 / 550 °C
Temperature Stability °C	±2 °C
UPC	4003019449323
Voltage	230V / 50Hz
Weight (Catalog)	1.9 kg

RT Pico



WX

RT Micro



WX



WT

RT Ultra




WX



Soldering Iron: WXPP ○ / WXPP MS ●

article a / b (mm) (inch)

Conical



RTP 001 C RTP 001 C		0.1 0.004
RTP 001 C NW RTP 001 C NW MS		0.1 0.004
RTP 002 C RTP 002 C MS		0.2 0.008
RTP 004 C RTP 004 C MS		0.4 0.016
RTP 001 C X RTP 001 C X MS		0.1 0.004
RTP 002 C X RTP 002 C X MS		0.2 0.008

Soldering Iron: WXMP ○ / WXMP MS ● / WMRP ○ / WMRP MS ●

article a / b (mm) (inch)



RTM 001 C NW RTM 001 C NW MS		0.1 0.004
RTM 002 C RTM 002 C MS		0.2 0.008
RTM 002 C L RTM 002 C L MS		0.2 0.008
RTM 004 C X MS		0.4 0.016
RTM 005 C X MS		0.5 0.019
RTM 008 C RTM 008 C MS		0.8 0.031

Soldering Iron: WXUP MS ●

article a / b (mm) (inch)

RTU 004 C MS		0.4 0.016
RTU 008 C MS		0.8 0.031
RTU 016 C MS		1.6 0.063
RTU 004 C X MS		0.4 0.016
RTU 008 C X MS		0.8 0.031
RTU 016 C X MS		1.6 0.063

Bevel Cut





RTP 004 B RTP 004 B MS		0.4 0.016
RTP 012 B RTP 012 B MS		1.2 0.047

RTM 004 B RTM 004 B MS		0.4 0.016
RTM 012 B RTM 012 B MS		1.2 0.047

RTU 020 B MS		2.0 0.079
RTU 035 B MS		3.5 0.138
RTU 050 B MS		5.0 0.197

Chisel



RTP 002 S RTP 002 S MS		0.2 / 0.1 0.008 / 0.004
RTP 002 S NW RTP 002 S NW MS		0.2 / 0.1 0.008 / 0.004
RTP 004 S RTP 004 S MS		0.4 / 0.2 0.016 / 0.008
RTP 008 S RTP 008 S MS		0.8 / 0.3 0.031 / 0.012
RTP 010 S RTP 010 S MS		1.0 / 0.3 0.039 / 0.012
RTP 013 S RTP 013 S MS		1.3 / 0.3 0.051 / 0.012

RTM 003 S		0.3 / 0.15 0.012 / 0.006
RTM 003 S NW RTM 003 S NW MS		0.3 / 0.1 0.012 / 0.004
RTM 004 S MS		0.4 / 0.2 0.016 / 0.008
RTM 006 S MS		0.6 / 0.4 0.024 / 0.016
RTM 008 S RTM 008 S MS		0.8 / 0.4 0.031 / 0.016
RTM 008 S X RTM 008 S X MS		0.8 / 0.4 0.031 / 0.016
RTM 010 S RTM 010 S MS		1.0 / 0.3 0.039 / 0.012
RTM 013 S RTM 013 S MS		1.3 / 0.4 0.051 / 0.016
RTM 013 S X RTM 013 S X MS		1.3 / 0.5 0.051 / 0.019
RTM 015 S RTM 015 S MS		1.5 / 0.4 0.059 / 0.016
RTM 018 S RTM 018 S MS		1.8 / 0.4 0.071 / 0.016
RTM 022 S RTM 022 S MS		2.2 / 0.4 0.087 / 0.016
RTM 032 S RTM 032 S MS		3.2 / 0.9 0.126 / 0.035
RTM 036 S RTM 036 S MS		3.6 / 0.9 0.141 / 0.035


RTU 015 S MS		1.5 / 0.4 0.059 / 0.016
RTU 022 S MS		2.2 / 0.6 0.087 / 0.024
RTU 032 S MS		3.2 / 0.8 0.126 / 0.031
RTU 032 S L MS		3.2 / 0.8 0.126 / 0.031
RTU 050 S MS		5.0 / 1.2 0.197 / 0.047
RTU 076 S MS		7.6 / 1.5 0.299 / 0.059
RTU 093 S MS		9.3 / 2.0 0.366 / 0.079

NO COMPROMISE.

PRECISION. PERFORMANCE. POWER.

EXPLORE THE NEW ACTIVE SOLDERING TIP RANGE



Knife



RTP 010 K RTP 010 K MS		1.0 0.039
RTP 010 K NW RTP 010 K NW MS		1.0 0.039
RTP 025 K RTP 025 K MS		2.5 0.098

RTM 025 K RTM 025 K MS		2.5 0.098
RTM 022 K RTM 022 K MS		2.2 0.087
RTM 030 K RTM 030 K MS		3.0 0.118

Gullwing



RTP 020 G RTP 020 G MS		2.0 0.079
---------------------------	--	--------------

RTM 020 G RTM 020 G MS		2.0 0.079
---------------------------	--	--------------

RTU 020 G MS		2.0 0.079
--------------	--	--------------

- Standard tip
- Mil-Spec soldering tip
- not wettable

Measuring tip



Blade



RTU 100 K MS		10.0 0.393
RTU 160 K MS		16.0 0.630
RTU 200 K MS		20.0 0.078
RTU 330 K MS		33.0 1.299

Weller®

www.weller-tools.com/nocompromise