

HT-EVG08 AUTO TRACKING CAMERA

กล้องติดตามผู้ประชุมอัตโนมัติ

- Super high-definition 2MP
- 20X optical zoom lens
- Low noise and High SNR
- PTZ Control
- Multiple remote controls
- Support Multiple Control Protocol
- 255 presets positions



OPTICAL PARAMETER		
Lens	SDI+HDMI Camera	USB3.0 +HDMI Camera
Sensor	SONY 1/2.8" IMX CMOS	
Effective Pixels	2.07 Megapixels	
Signal System	PAL/NTSC	
Resolution	1080P60/50/30/25/59.94 1080I60/50/59.94 720P60/50/59.94	HDMI: 1080P60/50/30/25/59.94 1080I60/50/59.94 720P60/50/59.94 USB3.0: 1080P60/50/30/25/;720P60/50/30/25
HOV	20X:58.7°(W) ~ 3.2°(T)	
Shortest View Distance	10mm(W) ~ 1000mm(T)	
Minimum Illumination	0.1Lux	
Exposure Control	Auto, Manual	
Shutter Speed	1/1s ~ 1/10,000s, 22 steps	
Gain	Manual	
White Balance	Auto, ATW, Indoor, Outdoor, Manual	
Noise-Signal Ratio	≥50db	
OSD Menu	Support	
MECHANICAL PARAMETER		
Pan-Tilt	Horizontal Angle: ±170°(Maximum speed: 100°/s) Vertical Angle: -30°to +90°(Maximum speed: 60°/s)	
No. of Preset Positions	255	
Preset Positions	Support	
INTERFACE		
Video Output	HDMI, HD-SDI(3G), RJ45	HDMI, USB3.0,RJ45
Control Interface	RS-232C(Mini 8-DIN)(VISCA IN and OUT), RS485	RS-232C(Mini 8-DIN),RS485
Control Protocol	VISCA, PELCO P/D	
Baud Rate	9600bps, 4800, 2400bps, 115200	
NETWORK PARAMETER		
Video Compression	H.264,H.265	
Frame Rate	1920*1080@30fps, 1280*720@30fps; 960*540@30fps, 640*480@30fps	
Video Compression Rate	100kbps-8Mbps Continuously Adjustable, Support CBR/VBR	
Data Storage	Video and Photos	
Storage Mechanism	Auto, Manual(Loop, Timing, Motion Detect)	
Protocols	TCP/IP, UDP, RTP, RTSP, RTCP, HTTP, DNS, DDNS, DHCP, FTP, NTP, UPNP,RTMP	
ONVIF	Support	
Browser	Higher Version than IE11	WWW.STARELECTRONIC.CO.TH